# **Professional Obstruction lighting controller**

APC-02





### PRODUCT DESCRIPTION

The APC-02 lighting controller is designed for obstruction lighting systems. It is equipped with four output circuits. The controller is designed to work with lamps powered by 24V DC. The controller enables automatic switching of the lamps in the event of a twilight sensor activation. Each circuit can be connected internally to a constant voltage or pulse output. This solution enables the implementation of obstruction lighting on several levels, where it is required to provide pulsed light on several levels and continuous light on other levels.

Each of the outputs is protected against short-circuit by an overcurrent breaker. The controller signals the failure of the output circuit.

## **PRODUCT APPLICATION**

Obstruction lighting control systems.

### **TECHNICAL DETAILS**

Producer: APS AVIATION

Producer code: APC-02

Power supply: 230V AC, 50 Hz

Power consumption: < 5W IP rating: IP65

Housing: Stainless steel

Mounting type: Mounting rails

Temperature range: -25°C to +55°C

Dimensions: 600 x 400 x 250 mm

Outputs: Max 4 pcs

Functions of the overcurrent protection for controller: each output

twilight sensor

steady state output or

pulsed output fault indicator realtip element sms monitoring surge protection humidity sensor temperature sensor

## **CERTIFICATES**



CE

